



LOW LOADERS

19 TONNE - 33 TONNE CAPACITY

DESIGNED TO PERFORM. BUILT TO LAST.



@redrockmachinery

www.redrockmachinery.com

Tel: (0044) 028 3755 2390

Redrock Machinery Ltd.
77 Redrock Road
Collone
Armagh
N. Ireland
BT60 2BL

AGRI LOW LOADERS

19T LOW LOADER



20T LOW LOADER

For the toughest jobs, you need the toughest trailers. The Redrock Agri Low Loader range is designed with affordability in mind, without sacrificing strength, durability or quality. With a 13 degree loading angle, loading and unloading is easily accomplished. Load carrying capacities are available in both 19 tonne (17.5ft flat + 5ft beaver) and 20 tonne (21ft flat + 2ft beaver) models.

Features include:

- Sprung ramps
- Weld in hitch
- Removeable headboard
- Full timber floor
- Full commercial 310×190 127mm round axle
- 215/75 R17.5 wheels

Optional Extras:

- Plastic tool box
- Hydraulic ramps
- 445/45 R19.5 wheels
- Bale rack
- Bale wedge
- Adjustable bolt-on hitch

INDUSTRIAL LOW LOADERS



For the toughest jobs, you need the toughest trailers. The Redrock Industrial Low Loader range is designed for strength, durability and a trouble free work life. This range is made with high-output customers in mind, containing a higher spec and more heavy duty design compared to our Agri Low Loaders. With a 13 degree loading angle, loading and unloading is easily accomplished. Load carrying capacities are available in both 22 tonne tandem axle (21ft flat + 2ft beaver) and 33 tonne tri-axle (23ft flat + 2ft beaver).

Redrock Trailers are fitted with high speed commercial axles as standard with 310×190 brakes giving approx 50% braking efficiency.

Hydraulic ramps are fitted as standard c/w hydraulic operating lever located at rear of trailer.

| | 22T Tandem Axle | 33T Tri Axle |
|--------------------|--------------------|--------------------|
| Load Capacity | 22 Tonne | 33 Tonne |
| Flat Bed Length | 21' (6400mm) | 23' (7010mm) |
| Beaver Tail Length | 2' (600mm) | 2' (600mm) |
| Width | 8'2" (2500mm) | 8'2" (2500mm) |
| Chassis | 254mm I Beam | 254mm I Beam |
| Outside Chimes | 200x75mm | 200x75mm |
| Tyres | 235/75 x 17.5 | 235/75 x 17.5 |
| Ramps | Hydraulic | Hydraulic |
| Drawbar | Sprung | Sprung |
| Axles | Commercial 310×190 | Commercial 310×190 |
| Brakes | Hydraulic | Air/Hydraulic |

REDROCK LOW LOADERS

DESIGNED TO PERFORM. BUILT TO LAST.



Due to our policy of continuous product improvement, Redrock Machinery reserve the right to alter the specification displayed on this brochure.



@redrockmachinery

www.redrockmachinery.com

Tel: (0044) 028 3755 2390

Redrock Machinery Ltd.
77 Redrock Road
Collone
Armagh
N. Ireland
BT60 2BL